

35 45 60 Plasma Cutters



PACKAGE CONTENTS

PLASMA POWER SOURCE **CUTSKILL 35 OR 45**

CutSkill 60A Plasma Torch

Work Cable and Clamp

Wrench for Air Filter

1x 1/4" Nitto Air Line Connector

PLASMA POWER SOURCE **CUTSKILL 60**

CutSkill 60A Plasma Torch

Gouging Tip 1.1mm

Work Cable and Clamp

Wrench for Air Filter

1x 1/4" Nitto Air Line Connector

Shoulder Strap

The 60A Torch includes everything to get cutting!

ORDERING INFORMATION

1-1601-30
1-1601-40
1-1601-60
CSP337000
CSP337001
CSP337002
CSP337095
CSP337003

CutSkill 60A Plasma Torch Standoff Guide	CSP337004
CutSkill 60A Plasma Torch Shield Cup	CSP337005
CutSkill 60A Plasma Torch 0-Ring	CSP337006
CutSkill 60A Plasma Torch Gas Diffuser	CSP337007
CutSkill 60A Plasma Torch Gouging Tip 1.1mm*	CSP337096
CutSkill Plasma Inline Filter	CSP337039
CutSkill Plasma Inline Filter Cartridge	CSP337040
CutSkill Plasma Circle Cutting Guide	CSP337041

^{*}For use with CutSkill 60 plasma System only.

WE RECOMMEND GENUINE CIGWELD PRODUCTS













THE BIGGEST RANGE AND THE BEST QUALITY, WITH GUARANTEED PERFORMANCE.

◎ Fi 🛩 🖸 CIGWELD.COM.AU

AN **ESAB** BRAND

CutSkill | CutSkill | CutSkill 354560 Plasma Gutters





MARKET FIRST INTERFACE

CIGWELD has now officially changed plasma cutting forever, with the launch of the new range of CutSkill Manual Plasma machines.

Over two years in development, the new CutSkill 35, CutSkill 45 and CutSkill 60 machines from CIGWELD feature a user interface that not only incorporates the latest in colour LCD technology, but also simplifies the entire cutting set up process.

With a single control knob, the operator can select each function necessary to suit their desired needs.

Decide if you want your torch set to manual or latch mode, whether you're cutting flat plate or grid plate, adjust your current and you're ready to cut! All of these actions are clearly displayed on the massive 2.8" colour LCD display. Need to gouge, then the CutSkill 60 has you covered!









LCD SCREEN

2.8" LCD screen displays all cutting setting, input voltage and input air pressure

- Ease of use for the user
- All key information at a glance
- Taking plasma cutting to a whole new level
- Single Control Knob adjusts all cutting settings





Talk about easy. The colour LCD interface told me everything I needed to know, without the need to adjust dials and buttons all over the unit like with other plasma cutters ""

REMOVABLE AIR FILTER WITH PURGING VALVE

Moisture in your air compressor can reduce the lifespan of the Plasma Torch consumables. The CutSkill inbuilt air filter removes this problem. The air filter can be purged at any time by using the purging valve and is also removable for cleaning. It is housed in a concave inset in order to prevent damage.

This unit packs a serious punch! It gets through steel like a knife through butter! ""





INTERNAL REGULATOR

The regulator is internal and air through the torch is managed automatically by the plasma unit. This removes the need to adjust air pressure for individual cutting requirements.

TORCH

All three Plasma CutSkill machines come complete with a detachable 60 amp torch with 5 meter lead designed specifically for the CutSkill plasma cutting range.

The torch includes a safety latch in order to prevent risk of accidental arc.

CONSUMABLES

Each of the high quality consumables is suitable for the CutSkill 35, CutSkill 45 or CutSkill 60, with the exception of the cutting and

ACCESSORIES

Inline Air Filter

The inline Air Filter is designed to prevent all moisture, plus oil and dirt down to 0.85 microns from passing through your air line to the plasma unit. This offers extra protection in addition to the inbuilt air filter located in the plasma unit itself.

Circle Cutting Guide

The Circle Cutting Guide allows for circle cutting up to a radius of 400mm. The cutting guide can be affixed to the work plate by either of the included Straight, Magnetic or Screw Pivots.

WARRANTY

3-Year Warranty on the power source.

FEATURES



Fully Compliant to AS 60974.1-2006. Enclosure rated to IP23S.



2.8" Colour LCD Screen Allows for full interactive digital control

CutSkill



Air Compressor

Recommended air compressor required: Cutskill 35 & 45 - 730kPa,12 CFM Cutskill 60 - 800kPa.12 CFM



Gouaina Tip Gouging Tip 1.1mm* *for CutSkill 60 System only

SPECIFICATIONS



YEARS*

3-Year Warranty' *Refer to operating manual for further details



CutSkill 60A Plasma Torch

	CutSkill 5
A CUTTER V	PLASMA CUTTER
7	

MILD STEEL CLEAN CUT: 20 mm 12 mm 16 mm MILD STEEL SEVERANCE: 16 mm 24 mm 28 mm STAINLESS CLEAN CUT: 10 mm 12 mm 14 mm **ALUMINIUM CLEAN CUT:** 12 mm 10 mm 8 mm 240V, 1Ph, PFC, 15A **INPUT POWER:** 240V, 1Ph, PFC, 10A 240V, 1Ph, PFC, 15A Minimum recommended circuit breaker is 25A **DUTY CYCLE:** 35% @ 35A 35% @ 45A 20% @ 60A** 35% **(7) CURRENT RANGE:** 20-35 Amps 20-45 Amps 20-60 Amps INPUT AIR REQUIRED: 800 kPa, 110 LPM kPa 730 kPa. 110 LPM 730 kPa, 110 LPM [4] GENERATOR REQUIRED: 8 kVA 9 kVA 15 kVA 415mm L x 176mm W x 415mm L x 176mm W x 437mm L x 176mm W x DIMENSIONS: 324mm H (Incl Handle) 324mm H (Incl Handle) 324mm H (Incl Handle) KG WEIGHT: 11.8 kg 11.8 kg 13.2kg

**Upgrade to 4mm² lead and 20A plug to achieve 30% @ 60A Duty Cycle.